



Marginal Loss Factors

2026/27



Purpose

Rule 146 of the Pilbara Network Rules (PNR) requires a covered Network Service Provider (NSP) to determine and from time-to-time review and revise the Loss Factors for each balancing point in its network and, if its network includes non-interval metered loads, a National Wholesale Meter. The values provided are purely for the purposes of energy balancing.

2026/27 Marginal Loss Factors

Table 1: 2026/27 Marginal Loss Factors

Connection Type	Name	Loss Factor 2026/27
Interconnection	BHP (MNM 702)	1.0109
Interconnection	BHP (MNM 709)	1.0109
Load	Roy Hill	1.003
Load	SWC FMG	1.003
Load	FMG Iron Bridge	1.0047
Interconnection	Rio - HP DMP 1	1.0135
Interconnection	Rio - HP DMP 2	1.0135
Interconnection	Rio - HP CLB CBS	1.0095
Interconnection	APA DEWAP - MDR	1.007
Generation	TransAlta SHPS	0.9953
Generation	ATCO KPS	1.0132

Implementation

These MLF values will take effect from 1st of July 2026. Horizon Power will continue to monitor system performance and conduct regular reviews to ensure MLF calculations remain accurate and reflective of actual network conditions.

Contact Information

Requests for determination of a Loss Factor for a new Connection Point, or for the reassessment of an existing Loss Factor in accordance with Rule 147(1) of the Pilbara Network Rules, should be submitted to Horizon Power via pilbara.network@horizonpower.com.au.